

PROPERTIES	AVERAGE VALUE
ASTM D1056 - 00	2C2
DENSITY	140 Kg m ³
COMPRESSION DEFLECTION 25% (35-63)	47 kPa
COMPRESSION SET 50% 22/H 20°C (25% MAX.)	22 %
ELONGATION – ASTM D412	170%
TEMPERATURE RANGE (CONSTANT)	- 40°C / + 120°C
WATER ABSORPTION	0.005%
TENSILE STRENGTH (KG/CM ³) – ASTM D412	6.2
HEAT AGEING – CHANGE IN COMPRESSION DEFLECTION 168 HRS @ 70°C - ±30%	18%
FIRE RESISTANCE – FMVSS 302 (BURN RATE <100MM)	Pass

Please Note:

The figures present on this specification sheet are average values. We recommend and will support evaluation prior to use to ascertain the suitability of the material for the application.

Material Properties

- Good sealing properties (air, dust and water migration)
- Excellent chemical and oil resistance
- Flexible and good recovery
- UL94 Approved

Neoprene sponge can be used across a wide range of applications and is mainly used to act as a water tight seal that is in contact with oil and petro-chemicals. Neoprene is extremely oil and chemical resistant and provides a superior seal compared to a lot of other closed cell materials. Neoprene also does not physically degrade at high or low temperatures, it hardens ensuring that the seal is still water tight under compression.

 **UK Industry Leader**
Of cellular solutions

 **Global Accreditation**
TS16949 & ISO14001

 **Experience of**
Over 50 years

Products & Services

Ramsay are a manufacturer of **die-cut** and **thermoformed** parts in technical high performance lightweight sponge, foams and fabrics. For sealing, NVH, thermal and acoustic applications to OEMs across industry and the world.

Die Cut Gaskets

Adhesive Tapes

Thermoforming

Fabrication & Assembly

From the moment your enquiry is received, Ramsay will offer technical support. Advising the best product and high performance material solution that suits your application and assembly process requirements.



Quality Assured

Ramsay are one of a few UK manufacturers with **TS16949, ISO9001 & IS14001** accreditations. All of our materials are registered in accordance with **IMDS** and are **ROSHH/REACH** compliant.

Our products are supplied in a condition of supply that complement our customer's process/assembly requirements, with product development and technical support from our project management team with full **APQP, FMEA** planning and **PPAP** approval.

We see our customers as partners, working together with a collaborative approach to ensure we continually improve our quality and overall service. We support our customers with further product development, on-site technical support and **VAVE** analysis/activity, enhancing customer competitiveness.

Get in Touch

Ramsay Rubber & Plastics Ltd
Vulcan Road, Bilston
West Midlands WV14 7HT
United Kingdom

T: +44 (0) 1902 407150

E: sales@ramsayrubber.com

W: www.ramsayrubber.com



FM 573015

EMS 652217

TS 573014